

dB Advanced LVT Underlay 3mm



LOW-PROFILE IMPACT PRODUCT

dB Advanced LVT Underlay is a high-density acoustic underlay designed for use under LVT, vinyl, lino and carpet tiles. Manufactured from natural cork and recycled rubber, it helps reduce impact and footfall noise while keeping floor build-up to a minimum. Suitable for prepared timber and concrete subfloors in residential and commercial applications.



Impact Reduction

17-33 dB*



Thickness

3mm



Roll Dimensions

1m x 15m



Area

15m²



Weight per Roll

27kg

*Reported result depends on the floor finish and tested build-up.
Actual installed performance varies with construction, detailing and workmanship.

SUITABLE FOR USE IN



HOME



WORK



LEISURE



EDUCATION



HEALTH

FEATURES

- ✓ Only 3mm thick - ideal where floor height is limited
- ✓ Suitable beneath LVT, vinyl, lino and carpet tiles
- ✓ Can be used over timber and concrete subfloors
- ✓ Natural cork and recycled rubber construction
- ✓ High density 600kg/m³
- ✓ Weight per roll 27kg
- ✓ Suitable for refurbishment and new build
- ✓ Compatible with suitable wet and electric underfloor heating
- ✓ Maximum 27°C at underlay level

IMPACT PERFORMANCE

Click LVT	17dB
Glue-down LVT	18dB
Sheet Vinyl	20dB
Carpet Tiles	33dB